


Caravelle Support Easy Height

Vitreous China 4.5/3 litre Dual Flush
Close-Coupled Toilet Suite

Designed for use with the patented
Caroma Orbital® Connector



Caravelle Support Easy Height



The **Caravelle Support Easy Height** suite comprises the Caravelle Support cistern matched with the Caravelle Easy Height pan. The cistern is moulded for back support and is fitted with dedicated raised care buttons. The 435mm extra height pan is suitable for Ambulant applications in domestic and light commercial projects. The pan connection system includes the patented Caroma Orbital® Connector for increased installation flexibility. The Caroma Orbital® Connector extends to any position in a 50mm radius, unlike traditional connectors that only move backwards and forwards. The setout range is from 90mm – 190mm with a recommended setout of 140mm. The suite meets “Deemed to Satisfy” criteria under AS1428.1-2009 as an alternative to the fully compliant Caroma Care 800 suite

- Pan:** **Caravelle Easy Height** 4.5 litre full flush washdown pan with boxed flushing rim. Caroma Orbital® connector supplied offering a range of set-outs.
- Traps:** S trap unvented.
- Cisterns:** **Caravelle Support** cistern – has a free fitting lid and is suitable for domestic and light commercial applications.
Vandal Resistant Conversion Kit – A simple to install conversion is available for the standard mechanism to lock lid onto the cistern, recommended for use in heavy duty commercial areas or when cistern is not installed against the wall. Code No.750109.
- Inlet Valve and Overflow:** **Standard Bottom Inlet Cistern** – available as right hand inlet which is interchangeable and incorporates Quietflow 2 inlet valve. Internal overflow only.
Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant.
- Fixing:** The cistern is fixed directly to the pan with a robust base fixing system without the need for wall fixing.
- Seats:** **Caravelle Care** single flap or double flap seat (white, sorrento blue or anthracite grey).
- Colours:** White only.
- Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

Caravelle Support Easy Height Toilet Suites with Caravelle Care Seat

Code No.	4.5/3 litre Bottom Inlet – Internal Overflow
987410	S-trap, Single Flap Seat
987420	S-trap, Double Flap Seat

Note: All height dimensions to underside of pan, make allowance for bedding when installing.

Bedding: The pan should be fixed to the floor with a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast drying cement in the bedding mixture. When bedded the back of the foot of the pan should be approximately 10mm above the finished floor.

Bracket fixing: The pan should be bedded with an acetic cured silicone sealant and fixed with the D82 Fixing Brackets supplied.