



Revision: 0

Date: October 2020


Supersedes all previous issues

Urbane II Cleanflush™

Vitreous China 4.5/3 litre Dual Flush Wall Faced
Close-Coupled Rimless Toilet Suite



cleanflush



Urbane II Cleanflush™



Back entry version of pan pictured



Bottom inlet version of pan pictured

Combining contemporary styling, industry leading rimless pan technology and GermGuard® Antibacterial Protection; a unique technology which kills harmful bacteria, Caroma Cleanflush™ is a superior flushing system suitable for domestic and commercial applications. Incorporating several patented technologies: Caroma Flow Splitter™, Caroma Flow Balancer™ and Caroma Uni-Orbital® Connector, the Cleanflush pan is innovative and the next evolution in toilets. The Flow Splitter evenly flows water around the top of the bowl to meet at the Flow Balancer which directs the water powerfully into the sump, reducing the need for brush cleaning. The rimless pan is easy to clean and unlike traditional pan profiles, provides full visibility of any grime build up. Caroma Cleanflush™ provides a cleaner clean for peace of mind.

Pan: Urbane Cleanflush™ wall faced close coupled 4.5 litre full flush rimless pan.

Traps: Universal trap for S or P-trap installations.

Cisterns: Urbane II close coupled cistern – has a free fitting lid and is suitable for domestic and light commercial applications. Available with internal overflow. Available in either back entry or bottom inlet options. Cistern inlet stop valve and inlet connection is concealed within the cistern and is included (back entry version only). **Vandal Resistant Conversion Kit** – A simple to install conversion is available for the standard mechanism to lock lid onto the cistern, recommended for use in heavy use commercial areas. Code No.750109.

Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant. Accurate wall setout for B.S.P. 1/2" Nipple water inlet connection is essential.

Buttons: The cistern button is supplied in Chrome (C) but other colour options are available: Black (B), Brushed Brass (BB), Brushed Nickel (BN), Gunmetal Grey (GM). Code No.687071.

Fixing: The cistern is fixed directly to the pan with a robust concealed base fixing system without the need for wall fixing.

Seats: The Vogue soft close quick release thermoset toilet seat with GermGuard® Antibacterial Protection; a unique technology which kills harmful bacteria, is provided as standard with seat caps in Stainless Steel (SS). Optional seat caps are available in 3 finishes, Brushed Brass (BB), Black (B) or Gunmetal Grey (GM). Code No.254213.

Colours: White only.

Installation: The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

