



SPECIFICATION

Surface Mounted Shelf Flat Top Series shall be fabricated of alloy 18-8 stainless steel, grade 304. Brackets shall be 16 gauge, shelf shall be 18 gauge, with 13mm lip on all four (4) sides. Front lip shall be hemmed under for safety. All exposed surfaces shall be No. 4 satin finish and shall be protected during shipment with a PVC film easily removable after installation. Structural assembly of shelf and bracket supports shall be of welded construction. Shelf shall be sized and brackets located as per standard schedule or shall be custom fabricated to customer supplied drawing.

| SCHEDULE OF AVAILABILITY | | | | | |
|----------------------------------|---------------------------|---------------------------|---|-----------|-----------------|
| SHELF DEPTH & MODEL SUFFIX ADDER | | | SHELF LENGTH DIMENSIONS & BRACKET SPACING | | |
| 125mm depth/length suffix | 150mm depth/length suffix | 200mm depth/length suffix | A=length | B=spacing | No. of brackets |
| -512 | -612 | -812* | 305mm | 150mm | 2 |
| -516 | -616 | | 410mm | 255mm | 2 |
| -518 | -624 | | 460mm | 305mm | 2 |
| -524 | | | 610mm | 460mm | 2 |
| -530 | | | 760mm | 305mm | 3 |

*Item 10-0692-812 is **NOT** Accessible Compliant

INSTALLATION

Unit is surface mounted on wall or partition using No. 10 self tapping screws (supplied by others) through holes provided in support brackets. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.

OPERATION

Shelf is stable and stationary after proper and secure mounting to adequate wall reinforcement or stud structure. Shelf is suitable for wet (self contained) or dry materials storage.

Surface Mounted Shelf Flat Top Series shall be Model No. 10-0692-xxx as supplied by ASI JD MacDonald.

WARRANTY

One year.

