


NOTE



Before drilling through the bench surface, check that there is a clear area directly underneath for the sprayer hose to retract. Allow 750mm for normal operation.



1

Using a 38mm hole saw, cut a neat hole through the bench top.


Remove the Inlet Boss, Lock Nut and Mounting Plates from the Threaded Inlet. Feed the Sprayer Hose through the hole and then position the mixer over the hole.



2

Slide the Mounting Plates onto the Threaded Inlet and fasten the Lock Nut.


Firmly fasten the Inlet Boss to the Threaded Inlet. Please ensure that the Rubber Gasket is still in the top of the Inlet Boss.



3


Attach the Counter Weight to the Sprayer Hose with the two screws supplied.

Adjust the Counter Weight to approximately 200mm from the bottom of the sprayer hose.




4

Connect the Sprayer Hose fitting to the Inlet Boss.



5


Connect hoses to the Mixer Inlets. Ensure that the Red Marked Hot Water Hose is connected to the inlet that is marked with Red Indicator Tape.



6

Connect hoses to the water supply.

CHECK AND TEST FOR LEAKS



recommended working pressure
150-500kPa
maximum hot water temperature
75 degrees

NOTE:

- If the pressure exceeds or is likely to exceed 550kPa, an approved pressure limiting device must be installed.
- Flush out all pipe work prior to installation.
- If the water temperature exceeds 75°C, an approved tempering valve must be fitted.
- Installation should comply with Australian standard AS3500.1 or relevant local authority requirements. Showers may not be suitable for use within:
 - Gravity-fed water systems

- Some instantaneous hot water systems; or
 - Pressure supply less than 150kPa;
- NOTE: The 500kPa maximum water supply pressure does not apply to fire service outlets.

Failure to comply with the above may void all warranties.

WARRANTY:

Please refer to the full warranty statement enclosed with the product before installing.

MAINTENANCE AND CARE:

- Chrome plated surfaces should be cleaned with mild liquid detergent or soap and water.
- Do not use cream cleaners or citrus based cleaning products, as they are abrasive.
- Use of unsuitable cleaning agents may damage the surface. Any damage caused in this way will not be covered by warranty.

DISCLAIMER:

While we aim to ensure the specifications shown are correct at the time of printing, we reserve the right to make modifications without prior notice. Always use the physical product measurements for mark-ups and roughing-in as the line drawing shown may differ from the actual product over time.

*All measurements are shown in millimeters.